EZ-Strip Spacer™

INSTALLATION INSTRUCTIONS

- Open box and remove one strip, cut to length or use full strip
- Peel back paper from double sided tape to expose adhesive Fig.1
- Place EZ-Strip Spacer[™] on the edge of the duct (The Manufacturer of Reflectix Insulation suggest placing spacers every 24 to 36 inches) Fig.2
- Repeat on all four sides Fig.3
- Wrap insulation around the duct overlapping the edges Fig.4
- R6 (small bubble) Use Zip-Ez Fasteners[™] down the seam, (just one per foot) securing the insulation Fig.5
- R8 (large bubble) Attach as per your manufactures instructions
- Tape the seams as per the manufacturers instructions
- For larger ducts add an EZ-Strip Spacer[™] down the center Fig.6
- For round pipe space EZ-Strip Spacers™ equally as shown Fig.7



Fig.3



Fig.2







J.T. Products, Inc. P.O. Box 626 Warwick, NY 10990

845.988.2000 Phone 845.988.2001 Fax www.jtproducts.com sales@jtproducts.com



tion

Easily Add Air Space to your Insulation

Cindustry Standard

onarv

the Revol

FAST INSTALLATION

-ENERGY SAVING

-EASY TO USE

-COST EFFECTIVE -COST EFFECTIVE -CLEAN NEAT PROFESSIONAL LOOK

PERMANENT HOLDING POWER

www.ezstripspacer.com

Fig.1