

2' X 2' PLASTIC DROP-IN RETURN



HT-2X2-RTN

MULTIPLE SIZE CAPABILITY

- 24" X 24" Lay in Return with Filter Grid
- Holds 20" X 20" X 1" or 20" X 20" X 2" filters (FILTER NOT INCLUDED)



- Cut Away Bulls-Eye Back with 6" - 16" Inlet Size Options—Compatible with HaVACo Quick Connect™ Start Collars (Shown at right) available in 6", 8", 10" and 12". Also compatible with other start collar brands.
- Standard White or Black Premix ABS – Won't chip, fade, or rust
- Includes packet of four (4) 1" stand offs — Peel off gasket back and stick on inside of Return Frame in each corner approximately 1" from each side to offer additional space between filter and inlet opening.



EASY INSTALLATION

1. Cut hole to appropriate diameter and insert start collar - to cut hole, cut slits perpendicular to the bulls-eye and use pliers to snap section. A 2-3" section can be easily snapped.
2. Install Return into drop ceiling grid.
3. When changing filter, release grille face at 2 clips, slowly lower until grille hangs at 90 degrees. Filter can be changed.
4. When cleaning grille face, swing grille face past 90 degrees to release from frame. Grille face and frame can be cleaned with mild detergent. Test on inconspicuous spot to avoid discoloration.



MADE IN THE USA



2' X 2' PLASTIC DROP-IN SUPPLY DIFFUSER



HT-2X2-SPL

BOOT DIAMETER OPTIONS

- 6" HT-2X2-SPL 6
- 8" HT-2X2-SPL 8
- 10" HT-2X2-SPL 10
- 12" HT-2X2-SPL 12



- 24" X 24" Drop-In with 3 Cone Diffuser
- Pre-molded 6" - 12" Inlet Boot Diameter Options
- Standard White or Black Premix ABS –Won't chip, fade, or rust
- 157X Less conductive than metal
- Quick Connect™ Easy Attach Knob for simple install and removal of diffuser for fast and efficient cleanability — Patent Pending



EASY INSTALLATION

1. Code Required 2" high boot - Easily attach to flex duct with cable tie.
2. Install Supply back into drop ceiling grid.
3. Insert Easy Attach Knob in grille face. Line up four guide pins in grille face with four receptors in Supply back. Screw in center knob to connect to crossbar in boot.
4. To remove grille face simply unscrew center knob. Grille face and Supply back can be cleaned with mild detergent. Test on inconspicuous spot to avoid discoloration.

MADE IN THE USA

